



TABLA DE CONDUCTORES ADMISIBLES EN TUBERÍA CONDUIT CABLES THW / THWN EN TUBERÍA CONDUIT METÁLICA

CALIBRE AWG O KCMIL	DIÁMETRO NOMINAL DEL TUBO (PULGADAS / MM)																	
	1/2"		3/4"		1"		1 1/4"		1 1/2"		2"		2 1/2"		3"		4"	
	16		21		27		35		41		53		63		78		103	
	THHN	THW	THHN	THW	THHN	THW	THHN	THW	THHN	THW	THHN	THW	THHN	THW	THHN	THW	THHN	THW
14	12	8	22	15	35	25	61	43	84	58	138	96	241	168	364	254	608	424
12	9	6	16	11	26	19	45	33	61	45	101	74	176	129	266	195	433	326
10	5	5	10	8	16	14	28	24	38	33	63	55	111	96	167	145	279	243
8	3	2	6	5	9	8	16	13	22	18	36	30	64	53	96	81	161	135
6	2	1	4	3	7	4	12	8	16	11	26	18	46	32	69	48	116	81
4	1	1	2	1	4	3	7	6	10	8	16	13	28	24	43	36	71	60
2	1	1	1	1	3	2	5	4	7	6	11	10	20	17	30	26	51	44
1	1	1	1	1	1	1	4	3	5	4	8	7	15	12	22	18	37	31
1/0	1		1	1	1	1	3	2	4	3	7	6	12	10	19	16	32	26
2/0			1	1	1	1	2	1	3	3	6	5	10	9	16	13	26	22
3/0			1	1	1	1	1	1	3	2	5	4	8	7	13	11	22	19
4/0			1		1	1	1	1	2	1	4	3	7	6	11	9	18	16
250					1	1	1	1	1	1	3	3	6	5	9	7	15	13
300					1	1	1	1	1	1	3	2	5	4	7	6	13	11
350					1		1	1	1	1	2	1	4	4	6	6	11	10
400							1	1	1	1	1	1	4	3	6	5	10	9
500							1	1	1	1	1	1	3	3	5	4	8	7
600							1	1	1	1	1	1	2	2	4	3	7	6